

CM 2478M

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
8 November 2001 (08.11.2001)

PCT

(10) International Publication Number  
WO 01/83657 A2(51) International Patent Classification<sup>7</sup>: C11D

(21) International Application Number: PCT/US01/07707

(22) International Filing Date: 9 March 2001 (09.03.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0010227.7 28 April 2000 (28.04.2000) GB(71) Applicant (for all designated States except US): **THE PROCTER & GAMBLE COMPANY** [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).(81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).**Published:**

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SOMERVILLE-ROBERTS, Nigel, Patrick** [GB/GB]; 3, The Cloggs, Ponteland, Newcastle upon Tyne NE20 9UJ (GB). **DASQUE, Bruno, Matthieu** [FR/GB]; 3 Swindon Terrace, Newcastle upon Tyne NE6 5RB (GB). **POUNDS, Thomas, John** [GB/GB]; 5 Grange Gardens, Grange Road, Cambridge CB3 9AT (GB).(74) Common Representative: **THE PROCTER & GAMBLE COMPANY**; c/o Reed, T., David, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).

WO 01/83657 A2

(54) Title: POUCHES COMPOSITIONS

(57) Abstract: The present invention relates to a multi-compartment pouch made from a water-soluble film and having at least two compartments, said multi-compartment pouch comprises a composition comprising a solid component and a liquid component, wherein at least one compartment comprises a solid component and at least one compartment comprises a liquid component.

## Pouched Compositions

### Field of the Invention

5

This invention relates to a pouch having at least two compartments, said pouch comprises a composition comprising a solid component and a liquid component, said solid and liquid components are contained in different compartments.

### Background to the Invention

10

Laundry detergent products can be found on the market to date in various forms, such as solid granular compositions and tablets, or liquid compositions. This gives the consumer a choice of detergent products they can use.

15

Some detergent ingredients currently used by the laundry industry, are preferably manufactured and processed in solid form, for example because these ingredients are water-insoluble and are difficult or costly to include in a liquid detergent composition, or because these materials are preferably transported and supplied in solid form and therefore require extra processing steps to enable them to be included in a liquid detergent composition. Such detergent ingredients include surfactants, hence these surfactants require extra processing steps to enable them to be included in liquid detergent compositions. Also, certain ingredients are formed into granular form and supplied and processed in solid form for stability reasons, for example certain enzyme prills.

25

Current methods of incorporating water-insoluble solid ingredients and ingredients typically supplied in solid form such as surfactants, into liquid detergent compositions include the use of emulsifiers, and dispersants. However, these liquid detergent compositions comprise only low amounts of these solid ingredients. For example, liquid detergent ingredients can comprise only low amounts of certain water-insoluble building

30

agents such as aluminosilicates or water-insoluble fabric softening agents such as clays, provided dispersants or emulsifiers are used.

However, it is desirable to include higher levels of water-insoluble solid ingredients such as water-insoluble building agents in a detergent composition with a substantial amount of liquid detergent ingredients. It is also desirable to be able to incorporate detergent ingredients that are typically transported in solid form, including granules comprising surfactants, in to a detergent composition comprising a substantial amount of liquid ingredients without the need for extra costly and difficult processing steps.

10

The inventors have found that by using a multi-compartment water-soluble pouch comprising at least two separate compartments, water-insoluble solid detergent ingredients can be included in a detergent composition comprising other liquid detergent ingredients, without the need for difficult, costly manufacturing and processing steps. The water-insoluble solid detergent ingredient is comprised by one compartment of a multi-compartment water-soluble pouch whilst the liquid detergent ingredients are comprised by another compartment of said pouch. Detergent compositions comprised by a multi-compartment water-soluble pouch in this way can comprise higher levels of water-insoluble solid detergent ingredients such as water insoluble building agent together with liquid detergent ingredients.

20

The inventors have also found that by using a multi-compartment water-soluble pouch comprising at least two separate compartments, detergent ingredients that are usually transported and supplied to the detergent manufacturers in solid form, such as agglomerates comprising surfactants, can be included in a detergent composition comprising substantial amounts of liquid detergent ingredients, without the need for difficult, costly manufacturing and processing steps. The solid detergent ingredients are comprised by one compartment of a multi-compartment water-soluble pouch whilst the liquid detergent ingredients are comprised by another compartment of said pouch.

30

#### Summary of the Invention

In a first embodiment of the invention, a multi-compartment pouch made from a water-soluble film and having at least two compartments, said multi-compartment pouch comprises a composition comprising a solid component and a liquid component, wherein;  
(a) a first compartment comprises a solid component comprising (by weight of the solid  
5 component) at least 10% water-insoluble solid material; and  
(b) a second compartment comprises a liquid component.

In a second embodiment of the invention, a multi-compartment pouch made from a water-soluble film and having at least two compartments, said multi-compartment pouch  
10 comprises a composition comprising a solid component and a liquid component, wherein;  
(a) a first compartment comprises a solid component comprising (by weight of the solid component) at least 15% particles which contain at least 20% by weight of the particle of surfactant; and  
(b) a second compartment comprises a liquid component.

15

#### Detailed Description of the Invention

##### Multi-compartment pouch and materials thereof

20 The multi-compartment pouch of the invention, herein referred to as "pouch", comprises at least two, preferably two compartments.

The pouch herein is typically a closed structure, made of materials described herein, enclosing a volume space which is separated into at least two compartments. The pouch  
25 comprises a composition comprising a liquid component and a solid component. The pouch and volume space thereof, can be of any form, shape and material which is suitable to hold the composition, e.g. without allowing the release of the composition from the pouch prior to contact of the pouch to water. The exact execution will depend on for example the type and amount of the composition in the pouch, the number of  
30 compartments in the pouch, the characteristics required from the pouch to hold, protect and deliver or release the compositions. Preferably, the pouch has a spheroid shape.

The pouch may be of such a size that it conveniently contains either a unit dose amount of the composition herein, suitable for the required operation, for example one wash, or only a partial dose, to allow the consumer greater flexibility to vary the amount used, for example depending on the size and/ or degree of soiling of the wash load.

5

The pouch is made from a water-soluble film which encloses an inner volume, said inner volume is divided into the compartments of the pouch.

10 The compartments of the pouch herein typically are closed structures made of a water-soluble film which encloses a volume space which comprises the components of the detergent composition. Said volume space is preferably enclosed by a water-soluble film in such a manner that the volume space is separated from the outside environment.

15 The solid component or liquid component that are comprised by a compartment of the pouch are contained in the volume space of the compartment, and are separated from the outside environment by a water-soluble film.

20 The term "separated" means for the purpose of this invention "physically distinct, in that a first ingredient comprised by a compartment is prevented from contacting a second ingredient if said second ingredient is not comprised by the same compartment which comprises said first ingredient".

25 The term "outside environment" means for the purpose of this invention, "anything which cannot pass through the material which encloses the compartment and which is not comprised by the compartment".

30 The compartment is suitable to hold the solid or liquid components of the composition, e.g. without allowing the release of the components from the compartment prior to contact of the pouch to water. The compartment can have any form or shape, depending on the nature of the material of the compartment, the nature of the components or composition, the intended use, amount of the components etc.

It may be preferred that the compartment which comprises the liquid component also comprises an air bubble, preferably the air bubble has a volume of no more than 50%, preferably no more than 40%, more preferably no more than 30%, more preferably no more than 20%, more preferably no more than 10% of the volume space of said  
5 compartment. Without being bound by theory, it is believed that the presence of the air bubble increases the tolerance of the pouch to the movement of liquid component within the compartment, thus reducing the risk of the liquid component leaking from the compartment.

10 The pouch is made from a water-soluble film, said water-soluble film typically has a solubility of at least 50%, preferably at least 75% or even at least 95%, as measured by the method set out hereinafter using a glass-filter with a maximum pore size of 50 microns, namely:

15 Gravimetric method for determining water-solubility of the material of the compartment and/or pouch:

10 grams  $\pm$  0.1 gram of material is added in a 400 ml beaker, whereof the weight has been determined, and 245ml  $\pm$  1ml of distilled water is added. This is stirred vigorously  
20 on magnetic stirrer set at 600 rpm, for 30 minutes. Then, the mixture is filtered through a folded qualitative sintered-glass filter with the pore sizes as defined above (max. 50 micron). The water is dried off from the collected filtrate by any conventional method, and the weight of the remaining polymer is determined (which is the dissolved or dispersed fraction). Then, the % solubility or dispersability can be calculated.

25

Preferred films are polymeric materials, preferably polymers which are formed into a film or sheet. The material in the form of a film can for example be obtained by casting, blow-moulding, extrusion or blow extrusion of the polymer material, as known in the art.

30 Preferred polymer copolymers or derivatives thereof are selected from polyvinyl alcohol (PVA), polyvinyl pyrrolidone, polyalkylene oxides, acrylamide, acrylic acid, cellulose, cellulose ethers, cellulose esters, cellulose amides, polyvinyl acetates, polycarboxylic

acids and salts, polyaminoacids or peptides, polyamides, polyacrylamide, copolymers of maleic/acrylic acids, polysaccharides including starch and gelatine, natural gums such as xanthum and carragum. More preferably the polymer is selected from polyacrylates and water-soluble acrylate copolymers, methylcellulose, carboxymethylcellulose sodium, dextrin, ethylcellulose, hydroxyethyl cellulose, hydroxypropyl methylcellulose, maltodextrin, polymethacrylates, most preferably polyvinyl alcohols, polyvinyl alcohol copolymers and hydroxypropyl methyl cellulose (HPMC). Preferably, the level of polymer in the film, for example a PVA polymer, is at least 60%.

- 10 The polymer can have any weight average molecular weight, preferably from about 1000 to 1,000,000, or even from 10,000 to 300,000 or even from 15,000 to 200,000 or even from 20,000 to 150,000.

Mixtures of polymers can also be used. This may in particular be beneficial to control the mechanical and/or dissolution properties of the compartment or pouch, depending on the application thereof and the required needs. For example, it may be preferred that a mixture of polymers is present in the material of the compartment, whereby one polymer material has a higher water-solubility than another polymer material, and/or one polymer material has a higher mechanical strength than another polymer material. It may be preferred that a mixture of polymers is used, having different weight average molecular weights, for example a mixture of PVA or a copolymer thereof of a weight average molecular weight of 10,000- 40,000, preferably around 20,000, and of PVA or copolymer thereof, with a weight average molecular weight of about 100,000 to 300,000, preferably around 150,000.

25

Also useful are polymer blend compositions, for example comprising hydrolytically degradable and water-soluble polymer blend such as polylactide and polyvinyl alcohol, achieved by the mixing of polylactide and polyvinyl alcohol, typically comprising 1-35% by weight polylactide and approximately from 65% to 99% by weight polyvinyl alcohol, if the material is to be water-dispersible, or water-soluble.

30

It may be preferred that the polymer present in the film is from 60-98% hydrolysed, preferably 80% to 90%, to improve the dissolution of the film.

Most preferred films are films which comprise a PVA polymer with similar properties to the film which comprises a PVA polymer and is known under the trade reference M8630, as sold by Chris-Craft Industrial Products of Gary, Indiana, US.

The film herein may comprise other additive ingredients than the polymer or polymer material. For example, it may be beneficial to add plasticisers, for example glycerol, ethylene glycol, diethyleneglycol, propylene glycol, sorbitol and mixtures thereof, additional water, disintegrating aids. It may be useful when the composition herein is a detergent composition, that the film itself comprises a detergent additive to be delivered to the wash water, for example organic polymeric soil release agents, dispersants, dye transfer inhibitors.

15

The compartment and preferably pouch as a whole are made from water-soluble material. Suitable examples of commercially available water-soluble materials include polyvinyl alcohol and partially hydrolysed polyvinyl acetate, alginates, cellulose ethers such as carboxymethylcellulose and methylcellulose, polyethylene oxide, polyacrylates and combinations of these.

20

### Composition

The pouch herein comprises a composition, typically said composition is contained in the volume space of the pouch.

25

Preferred compositions are cleaning compositions or fabric care compositions, preferably hard surface cleaners, more preferably laundry or dish washing compositions including, pre-treatment or soaking compositions and other rinse additive compositions.

30

Typically, the composition herein comprises such an amount of a cleaning composition, that one or a multitude of the pouched compositions is or are sufficient for one wash.



Preferably, the composition herein comprises at least one surfactant and at least one building agent.

- 5 The composition comprises a solid component and a liquid component. A first compartment comprises the solid component and a second compartment comprises the liquid component, so that the solid component and liquid component are separated by a water-soluble film.

10 Solid component

The solid component is comprised by a compartment of the pouch. Said compartment is a different compartment to the one that comprises the liquid component.

- 15 Typically, the solid component is substantially solid in that at least 90%, preferably at least 95%, more preferably at least 98% of the ingredients comprised by the solid component are in a solid form. Preferably the solid component comprises ingredients that are either difficult or costly to include in a substantially liquid composition or that are typically transported and supplied as solid ingredients which require additional  
20 processing steps to enable them to be included in a substantially liquid composition.

- Said solid component comprises (by weight of the solid component) at least 10%, more preferably at least 20%, more preferably at least 30%, more preferably at least 40%, more preferably at least 50%, more preferably at least 60%, more preferably at least 70%, more  
25 preferably at least 80% water-insoluble solid material.

- Water-insoluble solid material includes water-insoluble building agents, preferably the water-insoluble building agent is aluminosilicate, or water-insoluble fabric softening agents such as clay. Preferably, said water-insoluble solid material comprises a water-insoluble building agent. Preferred water-insoluble building agents are described in more  
30 detail hereinafter.

In another embodiment of the invention the solid component comprises (by weight of the solid component) at least 15%, or even at least 20%, or even at least 25%, or even at least 30%, or even at least 40%, or even at least 50%, or even at least 70% particles surfactant. Said agglomerate particles comprise at least 20%, preferably at least 40%, more preferably at least 60%, more preferably at least 80%, more preferably at least 90%, more preferably at least 95% surfactant. Typical surfactants for use in the present invention are described in more detail herein. The particle may be of any form, for example an agglomerate, spray-dried particle, extrudate or for example a surfactant flake consisting essentially of surfactant.

10

Said solid component preferably comprises at least one ingredient selected from the group consisting of building agent, chelating agent, bleaching agent, bleach activator, enzyme or enzyme prill, brightener, suds suppressor and dye. Said ingredients are in solid form, such as a particulate ingredient.

15

It may be possible that part or all of the ingredients of the solid component are not pre-granulated, such as agglomerated, spray-dried, extruded, prior to incorporation into the compartment, and that the component is a mixture of dry-mixed powder ingredients or even raw materials. Preferred may be that for example less than 60% or even less than 40% or even less than 20% of the component is a free-flowable pre-granulated granules.

20

#### Liquid component

The liquid component is comprised by a compartment of the pouch. Said compartment is a different compartment to the one that comprises the solid component.

25

Typically, the liquid component is substantially liquid in that at least 90%, more preferably at least 95%, %, more preferably at least 98% ingredients comprised by the liquid component are in a liquid form at room temperature.

30

The liquid component preferably comprises (by weight of the liquid component) at least 1% water-soluble perfume. The level of perfume comprised by the liquid composition is

preferably at least 2%, more preferably at least 5%, more preferably at least 10%, more preferably at least 40%.

5 Preferably, said liquid component comprises a solvent. Preferably said solvent is an alcohol/water or alcohol based solvent, more preferably said solvent contains or consists of ethanol and/or n-butoxy propoxy propanol. Preferably, said liquid component comprises (by weight of liquid component) from 0.1% to 30%, more preferably from 5% to 25%, more preferably from 10% to 20% solvent.

#### 10 Preferred ingredients of the liquid and solid components

As described above, in the composition the liquid component is substantially liquid (in that the liquid component comprises less than 10%, preferably less than 5%, more preferably less than 2% material in solid form at room temperature) and the solid  
15 component is substantially solid (in that the solid component comprises less than 10%, preferably less than 5%, more preferably less than 2% material in liquid form at room temperature). Thus, ingredients that are difficult or costly to include in a composition comprising a substantial amount of liquid ingredients are comprised by the solid component. The preferred amounts of ingredients described herein are % by weight of the  
20 whole composition and not % by weight of either the solid component or liquid component which comprise said ingredient.

#### Water insoluble building agent


25 The composition herein, especially the solid component of the composition herein preferably comprises a water-insoluble building agent.

Examples of water insoluble builders include the sodium aluminosilicates.

30 Suitable aluminosilicate zeolites have the unit cell formula  $\text{Na}_z[(\text{AlO}_2)_z(\text{SiO}_2)_y] \cdot x\text{H}_2\text{O}$  wherein z and y are at least 6; the molar ratio of z to y is from 1.0 to 0.5 and x is at least 5, preferably from 7.5 to 276, more preferably from 10 to 264. The aluminosilicate


material are in hydrated form and are preferably crystalline, containing from 10% to 28%, more preferably from 18% to 22% water in bound form.

The aluminosilicate zeolites can be naturally occurring materials, but are preferably synthetically derived. Synthetic crystalline aluminosilicate ion exchange materials are available under the designations Zeolite A, Zeolite B, Zeolite P, Zeolite X, Zeolite HS and mixtures thereof. Zeolite A has the formula:



wherein x is from 20 to 30, especially 27. Zeolite X has the formula  $\text{Na}_{86} [(\text{AlO}_2)_{86} (\text{SiO}_2)_{106}] \cdot 276 \text{H}_2\text{O}$ .

Preferred crystalline layered silicates for use herein have the general formula:



wherein M is sodium or hydrogen, x is a number from 1.9 to 4 and y is a number from 0 to 20. Crystalline layered sodium silicates of this type are disclosed in EP-A-0164514 and methods for their preparation are disclosed in DE-A-3417649 and DE-A-3742043. Herein, x in the general formula above preferably has a value of 2, 3 or 4 and is preferably 2. The most preferred material is  $\delta\text{-Na}_2\text{Si}_2\text{O}_5$ , available from Hoechst AG as NaSKS-6.

#### Water-insoluble fabric softening agents

The composition herein, especially the solid component thereof, preferably comprises a water-insoluble fabric softening agents. Such water-insoluble fabric softening agents include clays. Preferably the water-insoluble fabric softening agents are cationic compounds. Suitable cationic fabric softening agents include the water insoluble tertiary amines or dilong chain amide materials as disclosed in GB-A-1 514 276 and EP-B-0 011

340. Preferably, these water-insoluble tertiary amines or dilong chain amide materials are comprised by the solid component of the composition herein.

#### Detersive surfactants

5

#### Nonionic alkoxyalted surfactant

Essentially any alkoxyalted nonionic surfactants can be comprised by the composition herein. Those nonionic surfactants which are liquid at room temperature, are preferably  
10 included in the liquid component. The ethoxylated and propoxylated nonionic surfactants are preferred. Preferred alkoxyalted surfactants can be selected from the classes of the nonionic condensates of alkyl phenols, nonionic ethoxylated alcohols, nonionic ethoxylated/propoxylated fatty alcohols, nonionic ethoxylate/propoxylate condensates with propylene glycol, and the nonionic ethoxylate condensation products with propylene  
15 oxide/ethylene diamine adducts.

Highly preferred are nonionic alkoxyalted alcohol surfactants, being the condensation products of aliphatic alcohols with from 1 to 75 moles of alkylene oxide, in particular about 50 or from 1 to 15 moles, preferably to 11 moles, particularly ethylene oxide and/or  
20 propylene oxide, are highly preferred nonionic surfactants. The alkyl chain of the aliphatic alcohol can either be straight or branched, primary or secondary, and generally contains from 6 to 22 carbon atoms. Particularly preferred are the condensation products of alcohols having an alkyl group containing from 8 to 20 carbon atoms with from 2 to 9 moles and in particular 3 or 5 moles, of ethylene oxide per mole of alcohol.

25

#### Nonionic polyhydroxy fatty acid amide surfactant

Polyhydroxy fatty acid amides are highly preferred nonionic surfactant comprised by the composition, in particular those having the structural formula  $R^2CONR^1Z$  wherein :  $R^1$   
30 is H,  $C_{1-18}$ , preferably  $C_1$ - $C_4$  hydrocarbyl, 2-hydroxy ethyl, 2-hydroxy propyl, ethoxy, propoxy, or a mixture thereof, preferable  $C_1$ - $C_4$  alkyl, more preferably  $C_1$  or  $C_2$  alkyl,

most preferably  $C_1$  alkyl (i.e., methyl); and  $R_2$  is a  $C_5$ - $C_{31}$  hydrocarbyl, preferably straight-chain  $C_5$ - $C_{19}$  or  $C_7$ - $C_{19}$  alkyl or alkenyl, more preferably straight-chain  $C_9$ - $C_{17}$  alkyl or alkenyl, most preferably straight-chain  $C_{11}$ - $C_{17}$  alkyl or alkenyl, or mixture thereof; and Z is a polyhydroxyhydrocarbyl having a linear hydrocarbyl chain with at least 3 hydroxyls directly connected to the chain, or an alkoxyated derivative (preferably ethoxylated or propoxylated) thereof. Z preferably will be derived from a reducing sugar in a reductive amination reaction; more preferably Z is a glycityl.

A highly preferred nonionic polyhydroxy fatty acid amide surfactant for use herein is a  $C_{12}$ - $C_{14}$ , a  $C_{15}$ - $C_{17}$  and/or  $C_{16}$ - $C_{18}$  alkyl N-methyl glucamide.

It may be particularly preferred that the composition herein comprises a mixture of a  $C_{12}$ - $C_{18}$  alkyl N-methyl glucamide and condensation products of an alcohol having an alkyl group containing from 8 to 20 carbon atoms with from 2 to 9 moles and in particular 3 or 5 moles, of ethylene oxide per mole of alcohol.

The polyhydroxy fatty acid amide can be prepared by any suitable process. One particularly preferred process is described in detail in WO 9206984. A product comprising about 95% by weight polyhydroxy fatty acid amide, low levels of undesired impurities such as fatty acid esters and cyclic amides, and which is molten typically above about  $80^{\circ}\text{C}$ , can be made by this process.

#### Nonionic fatty acid amide surfactant

Fatty acid amide surfactants or alkoxyated fatty acid amides can also be comprised by the composition herein. They include those having the formula:  $R^6\text{CON}(R^7)(R^8)$  wherein  $R^6$  is an alkyl group containing from 7 to 21, preferably from 9 to 17 carbon or even 11 to 13 carbon atoms and  $R^7$  and  $R^8$  are each individually selected from the group consisting of hydrogen,  $C_1$ - $C_4$  alkyl,  $C_1$ - $C_4$  hydroxyalkyl, and  $-(C_2H_4O)_xH$ , where x is in the range of from 1 to 11, preferably 1 to 7, more preferably from 1-5, whereby it may

be preferred that  $R^7$  is different to  $R^8$ , one having x being 1 or 2, one having x being from 3 to 11 or preferably 5.

#### Nonionic alkyl esters of fatty acid surfactant


5

Alkyl esters of fatty acids can also be comprised by the composition herein. They include those having the formula:  $R^9COO(R^{10})$  wherein  $R^9$  is an alkyl group containing from 7 to 21, preferably from 9 to 17 carbon or even 11 to 13 carbon atoms and  $R^{10}$  is a  $C_1$ - $C_4$  alkyl,  $C_1$ - $C_4$  hydroxyalkyl, or  $-(C_2H_4O)_xH$ , where x is in the range of from 1 to 11, preferably 1 to 7, more preferably from 1-5, whereby it may be preferred that  $R^{10}$  is a methyl or ethyl group.

#### Nonionic alkylpolysaccharide surfactant

15 Alkylpolysaccharides can also be comprised by the composition herein, such as those disclosed in US Patent 4,565,647, Llenado, issued January 21, 1986, having a hydrophobic group containing from 6 to 30 carbon atoms and a polysaccharide, e.g., a polyglycoside, hydrophilic group containing from 1.3 to 10 saccharide units.

20 Preferred alkylpolyglycosides have the formula



wherein  $R^2$  is selected from the group consisting of alkyl, alkylphenyl, hydroxyalkyl, hydroxyalkylphenyl, and mixtures thereof in which the alkyl groups contain from 10 to 18 carbon atoms; n is 2 or 3; t is from 0 to 10, and x is from 1.3 to 8. The glycosyl is preferably derived from glucose.

#### Polyethylene/propylene glycols

30

The composition herein may comprise polyethylene and/or propylene glycol, particularly those of molecular weight 1000-10000, more particularly 2000 to 8000 and most preferably about 4000.

5    Anionic surfactant

The composition herein, preferably comprises one or more anionic surfactants. Any anionic surfactant useful for deterative purposes is suitable. Examples include salts (including, for example, sodium, potassium, ammonium, and substituted ammonium salts) such as mono-, di- and triethanolamine salts) of the anionic sulphate, sulphonate, 10    carboxylate and sarcosinate surfactants. Anionic sulphate surfactants are preferred.

Other anionic surfactants include the isethionates such as the acyl isethionates, N-acyl taurates, fatty acid amides of methyl tauride, alkyl succinates and sulfosuccinates, 15    monoesters of sulfosuccinate (especially saturated and unsaturated C<sub>12</sub>-C<sub>18</sub> monoesters) diesters of sulfosuccinate (especially saturated and unsaturated C<sub>6</sub>-C<sub>14</sub> diesters), N-acyl sarcosinates. Resin acids and hydrogenated resin acids are also suitable, such as rosin, hydrogenated rosin, and resin acids and hydrogenated resin acids present in or derived from tallow oil.

20

Anionic sulphate surfactant

Anionic sulphate surfactants suitable for use herein include the linear and branched primary and secondary alkyl sulphates, alkyl ethoxysulphates, fatty oleoyl glycerol 25    sulphates, alkyl phenol ethylene oxide ether sulphates, the C<sub>5</sub>-C<sub>17</sub> acyl-N-(C<sub>1</sub>-C<sub>4</sub> alkyl) and -N-(C<sub>1</sub>-C<sub>2</sub> hydroxyalkyl) glucamine sulphates, and sulphates of alkylpolysaccharides such as the sulphates of alkylpolyglucoside (the nonionic non-sulphated compounds being described herein).



Alkyl sulphate surfactants are preferably selected from the linear and branched primary C<sub>9</sub>-C<sub>22</sub> alkyl sulphates, more preferably the C<sub>11</sub>-C<sub>15</sub> branched chain alkyl sulphates and the C<sub>12</sub>-C<sub>14</sub> linear chain alkyl sulphates.

- 5 Alkyl ethoxysulfate surfactants are preferably selected from the group consisting of the C<sub>10</sub>-C<sub>18</sub> alkyl sulphates which have been ethoxylated with from 0.5 to 50 moles of ethylene oxide per molecule. More preferably, the alkyl ethoxysulfate surfactant is a C<sub>11</sub>-C<sub>18</sub>, most preferably C<sub>11</sub>-C<sub>15</sub> alkyl sulphate which has been ethoxylated with from 0.5 to 7, preferably from 1 to 5, moles of ethylene oxide per molecule.

10

#### Anionic sulphonate surfactant

- Anionic sulphonate surfactants suitable for use herein include the salts of C<sub>5</sub>-C<sub>20</sub> linear or branched alkylbenzene sulphonates, alkyl ester sulphonates, in particular methyl ester  
15 sulphonates, C<sub>6</sub>-C<sub>22</sub> primary or secondary alkane sulphonates, C<sub>6</sub>-C<sub>24</sub> olefin sulphonates, sulphonated polycarboxylic acids, alkyl glycerol sulphonates, fatty acyl glycerol sulphonates, fatty oleyl glycerol sulphonates, and any mixtures thereof.

#### Anionic carboxylate surfactant

20

Suitable anionic carboxylate surfactants include the alkyl ethoxy carboxylates, the alkyl polyethoxy polycarboxylate surfactants and the soaps ('alkyl carboxyls'), especially certain secondary soaps as described herein.

- 25 Suitable alkyl ethoxy carboxylates include those with the formula  $RO(CH_2CH_2O)_xCH_2COO-M^+$  wherein R is a C<sub>6</sub> to C<sub>18</sub> alkyl group, x ranges from 0 to 10, and the ethoxylate distribution is such that, on a weight basis, the amount of material where x is 0 is less than 20 % and M is a cation. Suitable alkyl polyethoxy polycarboxylate surfactants include those having the formula  $RO-(CHR_1-CHR_2-O)_x-R_3$  wherein R is a C<sub>6</sub> to C<sub>18</sub>  
30 alkyl group, x is from 1 to 25, R<sub>1</sub> and R<sub>2</sub> are selected from the group consisting of

hydrogen, methyl acid radical, succinic acid radical, hydroxysuccinic acid radical, and mixtures thereof, and  $R_3$  is selected from the group consisting of hydrogen, substituted or unsubstituted hydrocarbon having between 1 and 8 carbon atoms, and mixtures thereof.

- 5 Suitable soap surfactants include the secondary soap surfactants which contain a carboxyl unit connected to a secondary carbon. Preferred secondary soap surfactants for use herein are water-soluble members selected from the group consisting of the water-soluble salts of 2-methyl-1-undecanoic acid, 2-ethyl-1-decanoic acid, 2-propyl-1-nonanoic acid, 2-butyl-1-octanoic acid and 2-pentyl-1-heptanoic acid. Certain soaps may also be included  
10 as suds suppressers.

#### Alkali metal sarcosinate surfactant

- Other suitable anionic surfactants are the alkali metal sarcosinates of formula  $R-CON(R^1)CH_2COOM$ , wherein R is a  $C_5-C_{17}$  linear or branched alkyl or alkenyl group,  $R^1$   
15 is a  $C_1-C_4$  alkyl group and M is an alkali metal ion. Preferred examples are the myristyl and oleoyl methyl sarcosinates in the form of their sodium salts.

#### Cationic surfactant


- 20 Another preferred surfactant is a cationic surfactant, which may preferably be present at a level of from 0.1% to 60% by weight of the composition herein, more preferably from 0.4% to 20%, most preferably from 0.5% to 5% by weight.

- 25 When present, the ratio of the anionic surfactant to the cationic surfactant is preferably from 35:1 to 1:3, more preferably from 15:1 to 1:1, most preferably from 10:1 to 1:1.

- Preferably the cationic surfactant is selected from the group consisting of cationic ester surfactants, cationic mono-alkoxylated amine surfactants, cationic bis-alkoxylated amine  
30 surfactants and mixtures thereof.


Cationic mono-alkoxylated amine surfactants

Preferred cationic mono-alkoxylated amine surfactant for use herein, has the general  
 5 formula:



wherein  $\text{R}^1$  is an alkyl or alkenyl moiety containing from about 6 to about 18 carbon  
 10 atoms, preferably 6 to about 16 carbon atoms, most preferably from about 6 to about 11  
 carbon atoms;  $\text{R}^2$  and  $\text{R}^3$  are each independently alkyl groups containing from one to  
 about three carbon atoms, preferably methyl;  $\text{R}^4$  is selected from hydrogen (preferred),  
 methyl and ethyl,  $\text{X}^-$  is an anion such as chloride, bromide, methylsulphate, sulphate, or  
 the like, to provide electrical neutrality; A is selected from  $\text{C}_1$ - $\text{C}_4$  alkoxy, especially  
 15 ethoxy (i.e.,  $-\text{CH}_2\text{CH}_2\text{O}-$ ), propoxy, butoxy and mixtures thereof; and p is from 1 to  
 about 30, preferably 1 to about 15, most preferably 1 to about 8.

Highly preferred cationic mono-alkoxylated amine surfactants for use herein are of the  
 formula:




wherein  $\text{R}^1$  is  $\text{C}_6$ - $\text{C}_{18}$  hydrocarbyl and mixtures thereof, preferably  $\text{C}_6$ - $\text{C}_{14}$ , especially  
 $\text{C}_6$ - $\text{C}_{11}$  alkyl, preferably  $\text{C}_8$  and  $\text{C}_{10}$  alkyl, and X is any convenient anion to provide  
 25 charge balance, preferably chloride or bromide.

As noted, compounds of the foregoing type include those wherein the ethoxy (CH<sub>2</sub>CH<sub>2</sub>O) units (EO) are replaced by butoxy, isopropoxy [CH(CH<sub>3</sub>)CH<sub>2</sub>O] and [CH<sub>2</sub>CH(CH<sub>3</sub>O)] units (i-Pr) or n-propoxy units (Pr), or mixtures of EO and/or Pr and/or i-Pr units.

5

#### Cationic bis-alkoxylated amine surfactant

The cationic bis-alkoxylated amine surfactant for use herein, has the general formula:




10

wherein R<sup>1</sup> is an alkyl or alkenyl moiety containing from about 6 to about 18 carbon atoms, preferably 6 to about 16 carbon atoms, more preferably 6 to about 11, most preferably from about 8 to about 10 carbon atoms; R<sup>2</sup> is an alkyl group containing from one to three carbon atoms, preferably methyl; R<sup>3</sup> and R<sup>4</sup> can vary independently and are selected from hydrogen (preferred), methyl and ethyl, X<sup>-</sup> is an anion such as chloride, bromide, methylsulphate, sulphate, or the like, sufficient to provide electrical neutrality. A and A' can vary independently and are each selected from C<sub>1</sub>-C<sub>4</sub> alkoxy, especially ethoxy, (i.e., -CH<sub>2</sub>CH<sub>2</sub>O-), propoxy, butoxy and mixtures thereof; p is from 1 to about 30, preferably 1 to about 4 and q is from 1 to about 30, preferably 1 to about 4, and most preferably both p and q are 1.

20


Highly preferred cationic bis-alkoxylated amine surfactants for use herein are of the formula:



25

wherein  $R^1$  is  $C_6$ - $C_{18}$  hydrocarbyl and mixtures thereof, preferably  $C_6$ ,  $C_8$ ,  $C_{10}$ ,  $C_{12}$ ,  $C_{14}$  alkyl and mixtures thereof.  $X$  is any convenient anion to provide charge balance, preferably chloride. With reference to the general cationic bis-alkoxylated amine structure noted above, since in a preferred compound  $R^1$  is derived from (coconut)  $C_{12}$ - $C_{14}$  alkyl fraction fatty acids,  $R^2$  is methyl and  $ApR^3$  and  $A'qR^4$  are each monoethoxy.

Other cationic bis-alkoxylated amine surfactants useful herein include compounds of the formula:



wherein  $R^1$  is  $C_6$ - $C_{18}$  hydrocarbyl, preferably  $C_6$ - $C_{14}$  alkyl, independently  $p$  is 1 to about 3 and  $q$  is 1 to about 3,  $R^2$  is  $C_1$ - $C_3$  alkyl, preferably methyl, and  $X$  is an anion, especially chloride or bromide.

Other compounds of the foregoing type include those wherein the ethoxy ( $CH_2CH_2O$ ) units (EO) are replaced by butoxy (Bu), isopropoxy [ $CH(CH_3)CH_2O$ ] and [ $CH_2CH(CH_3)O$ ] units (i-Pr) or n-propoxy units (Pr), or mixtures of EO and/or Pr and/or i-Pr units.

#### Amphoteric surfactant

Suitable amphoteric surfactants for use herein include the amine oxide surfactants and the alkyl amphocarboxylic acids.

Suitable amine oxides include those compounds having the formula  $R^3(OR^4)_xN^0(R^5)_2$  wherein  $R^3$  is selected from an alkyl, hydroxyalkyl, acylamidopropoyl and alkyl phenyl

group, or mixtures thereof, containing from 8 to 26 carbon atoms;  $R^4$  is an alkylene or hydroxyalkylene group containing from 2 to 3 carbon atoms, or mixtures thereof;  $x$  is from 0 to 5, preferably from 0 to 3; and each  $R^5$  is an alkyl or hydroxyalkyl group containing from 1 to 3, or a polyethylene oxide group containing from 1 to 3 ethylene  
5 oxide groups. Preferred are  $C_{10}$ - $C_{18}$  alkyl dimethylamine oxide, and  $C_{10-18}$  acylamido alkyl dimethylamine oxide.

A suitable example of an alkyl aphodicarboxylic acid is Miranol(TM) C2M Conc. manufactured by Miranol, Inc., Dayton, NJ.

10

#### Zwitterionic surfactant

Zwitterionic surfactants can also be comprised by the composition herein. These surfactants can be broadly described as derivatives of secondary and tertiary amines,  
15 derivatives of heterocyclic secondary and tertiary amines, or derivatives of quaternary ammonium, quaternary phosphonium or tertiary sulfonium compounds. Betaine and sultaine surfactants are exemplary zwitterionic surfactants for use herein.

Suitable betaines are those compounds having the formula  $R(R')_2N^+R^2COO^-$  wherein  $R$   
20 is a  $C_6$ - $C_{18}$  hydrocarbyl group, each  $R^1$  is typically  $C_1$ - $C_3$  alkyl, and  $R^2$  is a  $C_1$ - $C_5$  hydrocarbyl group. Preferred betaines are  $C_{12-18}$  dimethyl-ammonio hexanoate and the  $C_{10-18}$  acylamidopropane (or ethane) dimethyl (or diethyl) betaines. Complex betaine surfactants are also suitable for use herein.

#### 25 Water-soluble building agent

The composition herein may comprises a water-soluble building agent, typically present at a level of from 0% to 36% by weight, preferably from 1% to 35% by weight, more preferably from 10% to 35%, even more preferably from 12% to 30% by weight of the  
30 composition or particle. Preferably, the water-soluble builder compound is an alkali or earth alkali metal salt of phosphate present at the level described above.

Other typical water-soluble building agents include the water soluble monomeric polycarboxylates, or their acid forms, homo or copolymeric polycarboxylic acids or their salts in which the polycarboxylic acid comprises at least two carboxylic radicals  
5 separated from each other by not more than two carbon atoms, borates, phosphates, and mixtures of any of the foregoing.

The carboxylate or polycarboxylate builder can be monomeric or oligomeric in type although monomeric polycarboxylates are generally preferred for reasons of cost and  
10 performance.

Suitable carboxylates containing one carboxy group include the water soluble salts of lactic acid, glycolic acid and ether derivatives thereof. Polycarboxylates containing two carboxy groups include the water-soluble salts of succinic acid, malonic acid,  
15 (ethylenedioxy) diacetic acid, maleic acid, diglycolic acid, tartaric acid, tartronic acid and fumaric acid, as well as the ether carboxylates and the sulfinyl carboxylates. Polycarboxylates containing three carboxy groups include, in particular, water-soluble citrates, aconitrates and citraconates as well as succinate derivatives such as the carboxymethyloxysuccinates described in British Patent No. 1,379,241, lactoxysuccinates  
20 described in British Patent No. 1,389,732, and aminosuccinates described in Netherlands Application 7205873, and the oxypolycarboxylate materials such as 2-oxa-1,1,3-propane tricarboxylates described in British Patent No. 1,387,447.

Polycarboxylates containing four carboxy groups include oxydisuccinates disclosed in  
25 British Patent No. 1,261,829, 1,1,2,2-ethane tetracarboxylates, 1,1,3,3-propane tetracarboxylates and 1,1,2,3-propane tetracarboxylates. Polycarboxylates containing sulfo substituents include the sulfosuccinate derivatives disclosed in British Patent Nos. 1,398,421 and 1,398,422 and in US Patent No. 3,936,448, and the sulphonated pyrolysed citrates described in British Patent No. 1,439,000. Preferred polycarboxylates are  
30 hydroxycarboxylates containing up to three carboxy groups per molecule, more particularly citrates.

Suitable examples of water-soluble phosphate builders are the alkali metal tripolyphosphates, sodium, potassium and ammonium pyrophosphate, sodium and potassium and ammonium pyrophosphate, sodium and potassium orthophosphate, sodium polymeta/phosphate in which the degree of polymerization ranges from about 6 to 21, and salts of phytic acid.

#### Peroxide Source

Another preferred ingredient is a perhydrate bleach, such as salts of percarbonates, particularly the sodium salts, and/ or organic peroxyacid bleach precursor. It has been found that when the pouch or compartment is formed from a material with free hydroxy groups, such as PVA, the preferred bleaching agent comprises a percarbonate salt and is preferably free from any perborate salts or borate salts. It has been found that borates and perborates interact with these hydroxy-containing materials and reduce the dissolution of the materials and also result in reduced performance.

Inorganic perhydrate salts are a preferred source of peroxide. Preferably these salts are present at a level of from 0.01% to 50% by weight, more preferably of from 0.5% to 30% by weight of the composition or component.

Examples of inorganic perhydrate salts include percarbonate, perphosphate, persulfate and persilicate salts. The inorganic perhydrate salts are normally the alkali metal salts. The inorganic perhydrate salt may be included as the crystalline solid without additional protection. For certain perhydrate salts however, the preferred executions of such granular compositions utilize a coated form of the material which provides better storage stability for the perhydrate salt in the granular product. Suitable coatings comprise inorganic salts such as alkali metal silicate, carbonate or borate salts or mixtures thereof, or organic materials such as waxes, oils, or fatty soaps.

Alkali metal percarbonates, particularly sodium percarbonate are preferred perhydrates herein. Sodium percarbonate is an addition compound having a formula corresponding to  $2\text{Na}_2\text{CO}_3 \cdot 3\text{H}_2\text{O}_2$ , and is available commercially as a crystalline solid.



Potassium peroxymonopersulfate is another inorganic perhydrate salt of use in the compositions herein.

5    Bleach / Bleach Activator

The composition herein preferably comprises a bleach activator, preferably comprising an organic peroxyacid bleach precursor. It may be preferred that the composition comprises at least two peroxy acid bleach precursors, preferably at least one hydrophobic  
10    peroxyacid bleach precursor and at least one hydrophilic peroxy acid bleach precursor, as defined herein. The production of the organic peroxyacid occurs then by an in situ reaction of the precursor with a source of hydrogen peroxide.

The bleach activator may alternatively, or in addition comprise a preformed peroxy acid  
15    bleach.

Preferably, at least one of the bleach activators, preferably a peroxy acid bleach precursor having an average particle size, by weight, of from 600 microns to 1400 microns, preferably from 700 microns to 1100 microns is present in the composition herein.

20    Hereby, it may be preferred that at least 80%, preferably at least 90% or even at least 95 % or even substantially 100% of the component or components comprising the bleach activator have a particle size of from 300 microns to 1700 microns, preferably from 425 microns to 1400 microns.

25    The hydrophobic peroxy acid bleach precursor preferably comprises a compound having a oxy-benzene sulphonate group, preferably NOBS, DOBS, LOBS and/ or NACA-OBS, as described herein.


30    The hydrophilic peroxy acid bleach precursor preferably comprises TAED, as described herein.

### Organic peroxyacid bleaching system


The composition herein preferably comprises an organic peroxyacid precursor. The production of the organic peroxyacid may occur by an in situ reaction of such a precursor with the percarbonate source. In an alternative preferred execution a pre-formed organic peroxyacid is incorporated directly into the composition.

### Peroxyacid bleach precursor

Peroxyacid bleach precursors are compounds which react with hydrogen peroxide in a perhydrolysis reaction to produce a peroxyacid. Generally peroxyacid bleach precursors may be represented as:



where L is a leaving group and X is essentially any functionality, such that on perhydrolysis the structure of the peroxyacid produced is:




Suitable peroxyacid bleach precursor compounds typically contain one or more N- or O-acyl groups, which precursors can be selected from a wide range of classes. Suitable classes include anhydrides, esters, imides, lactams and acylated derivatives of imidazoles and oximes. Examples of useful materials within these classes are disclosed in GB-A-1586789. Suitable esters are disclosed in GB-A-836988, 864798, 1147871, 2143231 and EP-A-0170386.


### Leaving groups

The leaving group, hereinafter L group, must be sufficiently reactive for the perhydrolysis reaction to occur within the optimum time frame (e.g., a wash cycle). However, if L is too reactive, this activator will be difficult to stabilize for use herein.

- 5 Preferred L groups are selected from the group consisting of:



10




- and mixtures thereof, wherein  $R^1$  is an alkyl, aryl, or alkaryl group containing from 1 to 14 carbon atoms,  $R^3$  is an alkyl chain containing from 1 to 8 carbon atoms,  $R^4$  is H or  $R^3$ , and Y is H or a solubilizing group. Any of  $R^1$ ,  $R^3$  and  $R^4$  may be substituted by

essentially any functional group including, for example alkyl, hydroxy, alkoxy, halogen, amine, nitrosyl, amide and ammonium or alkyl ammonium groups.

The preferred solubilizing groups are  $-\text{SO}_3^-\text{M}^+$ ,  $-\text{CO}_2^-\text{M}^+$ ,  $-\text{SO}_4^-\text{M}^+$ ,  $-\text{N}^+(\text{R}^3)_4\text{X}^-$  and  $\text{O}=\text{N}(\text{R}^3)_3$  and most preferably  $-\text{SO}_3^-\text{M}^+$  and  $-\text{CO}_2^-\text{M}^+$  wherein  $\text{R}^3$  is an alkyl chain containing from 1 to 4 carbon atoms, M is a cation which provides solubility to the bleach activator and X is an anion which provides solubility to the bleach activator. Preferably, M is an alkali metal, ammonium or substituted ammonium cation, with sodium and potassium being most preferred, and X is a halide, hydroxide, methylsulphate or acetate anion.

#### Amide substituted alkyl peroxyacid precursors

Amide substituted alkyl peroxyacid precursor compounds are suitable herein, including those of the following general formulae:




wherein  $\text{R}^1$  is an alkyl group with from 1 to 14 carbon atoms,  $\text{R}^2$  is an alkylene group containing from 1 to 14 carbon atoms, and  $\text{R}^5$  is H or an alkyl group containing 1 to 10 carbon atoms and L can be essentially any leaving group. Amide substituted bleach activator compounds of this type are described in EP-A-0170386.

#### Pre-formed organic peroxyacid

The organic peroxyacid bleaching system may contain a pre-formed organic peroxyacid.

A preferred class of organic peroxyacid compounds are the amide substituted compounds of the following general formulae:



wherein R<sup>1</sup> is an alkyl, aryl or alkaryl group with from 1 to 14 carbon atoms, R<sup>2</sup> is an  
 5 alkylene, arylene, and alkarylene group containing from 1 to 14 carbon atoms, and R<sup>5</sup> is  
 H or an alkyl, aryl, or alkaryl group containing 1 to 10 carbon atoms. Amide substituted  
 organic peroxyacid compounds of this type are described in EP-A-0170386.

Other organic peroxyacids include diacyl and tetraacylperoxides, especially  
 10 diperoxydodecanedioc acid, diperoxytetradecanedioc acid and diperoxyhexadecanedioc  
 acid. Mono- and diperazelaic acid, mono- and diperbrassylic acid and N-  
 phthaloylaminoperoxycaproic acid are also suitable herein.

#### Chelating agents or heavy metal ion sequestrant

15

The composition herein, preferably comprises as an optional ingredient, a chelating agent  
 or heavy metal ion sequestrant. By heavy metal ion sequestrant it is meant herein  
 components which act to sequester (chelate) heavy metal ions. These components may  
 also have calcium and magnesium chelation capacity, but preferentially they show  
 20 selectivity to binding heavy metal ions such as iron, manganese and copper.

Heavy metal ion sequestrants are generally present at a level of from 0.05% to 2%,  
 preferably from 0.1% to 1.5%, more preferably from 0.25% to 1.2% and most preferably  
 from 0.5% to 1% by weight of the composition herein.

25

Suitable heavy metal ion sequestrants for use herein include organic phosphonates, such  
 as the amino alkylene poly (alkylene phosphonates), alkali metal ethane 1-hydroxy  
 bisphosphonates and nitrilo trimethylene phosphonates.

Preferred among the above species are diethylene triamine penta (methylene phosphonate), ethylene diamine tri (methylene phosphonate) hexamethylene diamine tetra (methylene phosphonate) and hydroxy-ethylene 1,1 diphosphonate.

- 5 Other suitable heavy metal ion sequestrant for use herein include nitrilotriacetic acid and polyaminocarboxylic acids such as ethylenediaminetetracetic acid, ethylenetriamine pentacetic acid, ethylenediamine disuccinic acid, ethylenediamine diglutaric acid, 2-hydroxypropylenediamine disuccinic acid or any salts thereof. Especially preferred is ethylenediamine-N,N'-disuccinic acid (EDDS) or the alkali metal, alkaline earth metal,  
10 ammonium, or substituted ammonium salts thereof, or mixtures thereof.

- Other suitable heavy metal ion sequestrants for use herein are iminodiacetic acid derivatives such as 2-hydroxyethyl diacetic acid or glyceryl imino diacetic acid, described in EP-A-317,542 and EP-A-399,133. The iminodiacetic acid-N-2-  
15 hydroxypropyl sulfonic acid and aspartic acid N-carboxymethyl N-2-hydroxypropyl-3-sulfonic acid sequestrants described in EP-A-516,102 are also suitable herein. The  $\beta$ -alanine-N,N'-diacetic acid, aspartic acid-N,N'-diacetic acid, aspartic acid-N-monoacetic acid and iminodisuccinic acid sequestrants described in EP-A-509,382 are also suitable.

- 20 EP-A-476,257 describes suitable amino based sequestrants. EP-A-510,331 describes suitable sequestrants derived from collagen, keratin or casein. EP-A-528,859 describes a suitable alkyl iminodiacetic acid sequestrant. Dipicolinic acid and 2-phosphonobutane-1,2,4-tricarboxylic acid are also suitable. Glycinamide-N,N'-disuccinic acid (GADS), ethylenediamine-N,N'-diglutaric acid (EDDG) and 2-hydroxypropylenediamine-N,N'-  
25 disuccinic acid (HPDDS) are also suitable.

### Enzyme

- Another preferred optional ingredient useful in the composition herein, is one or more  
30 additional enzymes.

Preferred additional enzymatic materials include the commercially available lipases, cutinases, amylases, neutral and alkaline proteases, esterases, cellulases, pectinases, lactases and peroxidases conventionally incorporated into compositions. Suitable enzymes are discussed in US Patents 3,519,570 and 3,533,139.

5

Preferred commercially available protease enzymes include those sold under the tradenames Alcalase, Savinase, Primase, Durazym, and Esperase by Novo Industries A/S (Denmark), those sold under the tradename Maxatase, Maxacal and Maxapem by Gist-Brocades, those sold by Genencor International, and those sold under the tradename Opticlean and Optimase by Solvay Enzymes. Protease enzyme may be incorporated into the composition herein at a level of from 0.0001% to 4% active enzyme by weight of the composition.

Preferred amylases include, for example,  $\alpha$ -amylases obtained from a special strain of B licheniformis, described in more detail in GB-1,269,839 (Novo). Preferred commercially available amylases include for example, those sold under the tradename Rapidase by Gist-Brocades, and those sold under the tradename Termamyl and BAN by Novo Industries A/S. Amylase enzyme may be incorporated into the composition herein at a level of from 0.0001% to 2% active enzyme by weight of the composition.

20

Lipolytic enzyme may be present at levels of active lipolytic enzyme of from 0.0001% to 10% by weight of the particle, preferably 0.001% to 3% by weight of the composition, most preferably from 0.001% to 0.5% by weight of the compositions.

25 The lipase may be fungal or bacterial in origin being obtained, for example, from a lipase producing strain of Humicola sp., Thermomyces sp. or Pseudomonas sp. including Pseudomonas pseudoalcaligenes or Pseudomas fluorescens. Lipase from chemically or genetically modified mutants of these strains are also useful herein. A preferred lipase is derived from Pseudomonas pseudoalcaligenes, which is described in Granted European  
30 Patent, EP-B-0218272.

Another preferred lipase herein is obtained by cloning the gene from Humicola lanuginosa and expressing the gene in Aspergillus oryza, as host, as described in European Patent Application, EP-A-0258 068, which is commercially available from Novo Industri A/S, Bagsvaerd, Denmark, under the trade name Lipolase. This lipase is  
5 also described in US Patent 4,810,414, Hoge-Jensen et al, issued March 7, 1989.

#### Suds suppressing system

The composition may comprise a suds suppresser at a level less than 10%, preferably  
10 0.001% to 10%, preferably from 0.01% to 8%, most preferably from 0.05% to 5%, by weight of the composition. Preferably the suds suppresser is either a soap, paraffin, wax, or any combination thereof. If the suds suppresser is a suds suppressing silicone, then the detergent composition preferably comprises from 0.005% to 0.5% by weight a suds suppressing silicone.

15

Suitable suds suppressing systems for use herein may comprise essentially any known antifoam compound, including, for example silicone antifoam compounds and 2-alkyl alcanol antifoam compounds.

20 By antifoam compound it is meant herein any compound or mixtures of compounds which act such as to depress the foaming or sudsing produced by a solution of the composition herein, particularly in the presence of agitation of that solution.

Particularly preferred antifoam compounds for use herein are silicone antifoam  
25 compounds defined herein as any antifoam compound including a silicone component. Such silicone antifoam compounds also typically contain a silica component. The term "silicone" as used herein, and in general throughout the industry, encompasses a variety of relatively high molecular weight polymers containing siloxane units and hydrocarbyl group of various types. Preferred silicone antifoam compounds are the siloxanes,  
30 particularly the polydimethylsiloxanes having trimethylsilyl end blocking units. Preferably the composition herein comprises from 0.005% to 0.5% by weight suds suppressing silicone.



Other suitable antifoam compounds, in particular for the liquid component, include the monocarboxylic fatty acids and soluble salts thereof. These materials are described in US Patent 2,954,347, issued September 27, 1960 to Wayne St. John. The monocarboxylic fatty acids, and salts thereof, for use as suds suppresser typically have hydrocarbyl chains of 10 to 24 carbon atoms, preferably 12 to 18 carbon atoms. Suitable salts include the alkali metal salts such as sodium, potassium, and lithium salts, and ammonium and alkanolammonium salts.

Other suitable antifoam compounds include, for example, high molecular weight fatty esters (e.g. fatty acid triglycerides), fatty acid esters of monovalent alcohols, aliphatic C<sub>18</sub>-C<sub>40</sub> ketones (e.g. stearone) N-alkylated amino triazines such as tri- to hexa-alkylmelamines or di- to tetra alkyl diamine chlortriazines formed as products of cyanuric chloride with two or three moles of a primary or secondary amine containing 1 to 24 carbon atoms, propylene oxide, bis stearic acid amide and monostearyl di-alkali metal (e.g. sodium, potassium, lithium) phosphates and phosphate esters.

A preferred suds suppressing system in particular for inclusion in the solid component, comprises:

- (a) antifoam compound, preferably silicone antifoam compound, most preferably a silicone antifoam compound comprising in combination:
    - (i) polydimethyl siloxane, at a level of from 50% to 99%, preferably 75% to 95% by weight of the silicone antifoam compound; and
    - (ii) silica, at a level of from 1% to 50%, preferably 5% to 25% by weight of the antifoam compound;
- wherein said silica/silicone antifoam compound is incorporated at a level of less than 5%, preferably 0.01% to 5%, more preferably 0.05% to 4%, even more preferably 0.1% to 3%, by weight;

- 5 (b) a dispersant compound, most preferably comprising a silicone glycol rake copolymer with a polyoxyalkylene content of 72-78% and an ethylene oxide to propylene oxide ratio of from 1:0.9 to 1:1.1, at a level of less than 5%, preferably 0.01% to 5%, more preferably 0.05% to 4%, even more preferably 0.1% to 3%, by weight; a particularly preferred silicone glycol rake copolymer of this type is DCO544, commercially available from DOW Corning under the tradename DCO544;
- 10 (c) an inert carrier fluid compound, most preferably comprising a C<sub>16</sub>-C<sub>18</sub> ethoxylated alcohol with a degree of ethoxylation of from 5 to 50, preferably 8 to 15, at a level of less than 5%, preferably 0.01% to 5%, more preferably 0.05% to 4%, even more preferably 0.1% to 3%, by weight;
- 15 A highly preferred particulate suds suppressing system is described in EP-A-0210731 and comprises a silicone antifoam compound and an organic carrier material having a melting point in the range 50°C to 85°C, wherein the organic carrier material comprises a monoester of glycerol and a fatty acid having a carbon chain containing from 12 to 20 carbon atoms. EP-A-0210721 discloses other preferred particulate suds suppressing
- 20 systems wherein the organic carrier material is a fatty acid or alcohol having a carbon chain containing from 12 to 20 carbon atoms, or a mixture thereof, with a melting point of from 45°C to 80°C.

#### Polymeric dye transfer inhibiting agents

25


The composition herein may also comprise from 0.01% to 10 %, preferably from 0.05% to 0.5% by weight of polymeric dye transfer inhibiting agents. These polymeric dye transfer inhibiting agents are in addition to the polymeric material of the water-soluble film.

30


The polymeric dye transfer inhibiting agents are preferably selected from polyamine N-oxide polymers, copolymers of N-vinylpyrrolidone and N-vinylimidazole, polyvinylpyrrolidone polymers or combinations thereof.

5 a) Polyamine N-oxide polymers

Polyamine N-oxide polymers suitable for use herein contain units having the following structure formula :




wherein P is a polymerisable unit, and




R are aliphatic, ethoxylated aliphatics, aromatic, heterocyclic or alicyclic groups or any combination thereof whereto the nitrogen of the N-O group can be attached or wherein the nitrogen of the N-O group is part of these groups.

20 The N-O group can be represented by the following general structures :



or



wherein R<sub>1</sub>, R<sub>2</sub>, and R<sub>3</sub> are aliphatic groups, aromatic, heterocyclic or alicyclic groups or combinations thereof, x or/and y or/and z is 0 or 1 and wherein the nitrogen of the N-O group can be attached or wherein the nitrogen of the N-O group forms part of these groups. The N-O group can be part of the polymerisable unit (P) or can be attached to the polymeric backbone or a combination of both.

Suitable polyamine N-oxides wherein the N-O group forms part of the polymerisable unit comprise polyamine N-oxides wherein R is selected from aliphatic, aromatic, alicyclic or heterocyclic groups. One class of said polyamine N-oxides comprises the group of polyamine N-oxides wherein the nitrogen of the N-O group forms part of the R-group. Preferred polyamine N-oxides are those wherein R is a heterocyclic group such as pyridine, pyrrole, imidazole, pyrrolidine, piperidine, quinoline, acridine and derivatives thereof.

Other suitable polyamine N-oxides are the polyamine oxides whereto the N-O group is attached to the polymerisable unit. A preferred class of these polyamine N-oxides comprises the polyamine N-oxides having the general formula (I) wherein R is an aromatic, heterocyclic or alicyclic groups wherein the nitrogen of the N-O functional group is part of said R group. Examples of these classes are polyamine oxides wherein R is a heterocyclic compound such as pyridine, pyrrole, imidazole and derivatives thereof.

The polyamine N-oxides can be obtained in almost any degree of polymerization. The degree of polymerization is not critical provided the material has the desired water-solubility and dye-suspending power. Typically, the average molecular weight is within the range of 500 to 1000,000.

#### b) Copolymers of N-vinylpyrrolidone and N-vinylimidazole

Suitable herein are co-polymers of N-vinylimidazole and N-vinylpyrrolidone having an average molecular weight range of from 5,000 to 50,000. The preferred copolymers have a molar ratio of N-vinylimidazole to N-vinylpyrrolidone from 1 to 0.2.

c) Polyvinylpyrrolidone

The composition herein may also utilize polyvinylpyrrolidone ("PVP") having an average molecular weight of from 2,500 to 400,000. Suitable polyvinylpyrrolidones are commercially available from ISP Corporation, New York, NY and Montreal, Canada under the product names PVP K-15 (viscosity molecular weight of 10,000), PVP K-30 (average molecular weight of 40,000), PVP K-60 (average molecular weight of 160,000), and PVP K-90 (average molecular weight of 360,000). PVP K-15 is also available from ISP Corporation. Other suitable polyvinylpyrrolidones which are commercially available from BASF Co-operation include Sokalan HP 165 and Sokalan HP 12.

d) Polyvinylloxazolidone

The composition herein may also utilize polyvinylloxazolidones as polymeric dye transfer inhibiting agents. Said polyvinylloxazolidones have an average molecular weight of from 2,500 to 400,000.


e) Polyvinylimidazole

The composition herein may also utilize polyvinylimidazole as polymeric dye transfer inhibiting agent. Said polyvinylimidazoles preferably have an average molecular weight of from 2,500 to 400,000.

Optical Brightener

The composition herein may also optionally comprise from 0.005% to 5% by weight of certain types of hydrophilic optical brighteners.

Hydrophilic optical brighteners useful herein include those having the structural formula:



wherein R<sub>1</sub> is selected from anilino, N-2-bis-hydroxyethyl and NH-2-hydroxyethyl; R<sub>2</sub> is selected from N-2-bis-hydroxyethyl, N-2-hydroxyethyl-N-methylamino, morphilino, chloro and amino; and M is a salt-forming cation such as sodium or potassium.

When in the above formula, R<sub>1</sub> is anilino, R<sub>2</sub> is N-2-bis-hydroxyethyl and M is a cation such as sodium, the brightener is 4,4',-bis[(4-anilino-6-(N-2-bis-hydroxyethyl)-s-triazine-2-yl)amino]-2,2'-stilbenedisulfonic acid and disodium salt. This particular brightener species is commercially marketed under the tradename Tinopal-UNPA-GX by Ciba-Geigy Corporation. Tinopal-UNPA-GX is the preferred hydrophilic optical brightener useful in the compositions herein.

When in the above formula, R<sub>1</sub> is anilino, R<sub>2</sub> is N-2-hydroxyethyl-N-2-methylamino and M is a cation such as sodium, the brightener is 4,4'-bis[(4-anilino-6-(N-2-hydroxyethyl-N-methylamino)-s-triazine-2-yl)amino]-2,2'-stilbenedisulfonic acid disodium salt. This particular brightener species is commercially marketed under the tradename Tinopal 5BM-GX by Ciba-Geigy Corporation.

When in the above formula, R<sub>1</sub> is anilino, R<sub>2</sub> is morphilino and M is a cation such as sodium, the brightener is 4,4'-bis[(4-anilino-6-morphilino-s-triazine-2-yl)amino]-2,2'-stilbenedisulfonic acid, sodium salt. This particular brightener species is commercially marketed under the tradename Tinopal AMS-GX by Ciba Geigy Corporation.

Other optional ingredients

Other optional ingredients suitable for inclusion in the composition herein include perfumes, colours and filler salts, with sodium sulphate being a preferred filler salt.

#### Laundry washing method

5

Preferably, the multi-compartment pouch dissolves or disintegrates in water to deliver the solid detergent ingredients and liquid detergent ingredients to the washing cycle. Typically, the multi-compartment pouch is added to the dispensing draw, or alternatively to the drum, of an automatic washing machine.

10

Preferably, the multi-compartment pouch comprises all of the detergent ingredients of the detergent composition used in the washing. Although it may be preferred that some detergent ingredients are not comprised by the multi-compartment pouch and are added to the washing cycle separately. In addition, one or more detergent compositions other than the detergent composition comprised by the multi-compartment pouch can be used during the laundering process, such that said detergent composition comprised by the multi-compartment pouch is used as a pre-treatment, main-treatment, post-treatment or a combination thereof during such a laundering process.

20

#### Examples

##### Example I

A piece of plastic is placed in a mould to act as a false bottom. The mould consists of a cylindrical shape and has a diameter of 45mm and a depth of 25mm. A 1mm thick layer of rubber is present around the edges of the mould. The mould has some holes in the mould material to allow a vacuum to be applied. With the false bottom in place the depth of the mould is 12mm. A piece of Chris-Craft M-8630 film is placed on top of this mould and fixed in place. A vacuum is applied to pull the film into the mould and pull the film flush with the inner surface of the mould and the false bottom. 5ml of the liquid component of a detergent composition is poured into the mould. Next, a second piece of Chris-Craft M-8630 film is placed over the top of the mould with the liquid component

and sealed to the first piece of film by applying an annular piece of flat metal of an inner diameter of 46mm and heating that metal under moderate pressure onto the ring of rubber at the edge of the mould to heat-seal the two pieces of film together to form a compartment comprising the liquid component. The metal ring is typically heated to a temperature of from 135°C to 150°C and applied for up to 5 seconds.

The compartment comprising the liquid compartment is removed from the mould and the piece of plastic acting as a false bottom is also removed from the mould. A third piece of Chris-Craft M-8630 film is placed on top of the mould and fixed in place. A vacuum is applied to pull the film into the mould and pull the film flush with the inner surface of the mould. 40g of the solid component of the detergent composition is poured into the mould. Next, the compartment comprising the liquid component is placed over the top of the mould with the solid component and is sealed to the third layer of film by applying an annular piece of flat metal of an inner diameter of 46mm and heating that metal under moderate pressure onto the ring of rubber at the edge of the mould to heat-seal the pieces of film together to form a pouch comprising two compartments, where a first compartment comprises the liquid component of the detergent composition and a second compartment comprises the solid component of the detergent composition. The metal ring is typically heated to a temperature of from 135°C to 150°C and applied for up to 5 seconds.

### Example II

A pouch was made by the process described in example I which comprises the following liquid component and solid component.

	<u>Solid component detergent ingredient</u>	<u>Amount (by weight of the Solid component)</u>
	Zeolite	40%
30	Surfactant	11%
	Bleach	20%
	Chelating agent	0.8%



	Enzyme	6%
	Suds suppressor	1%
	Bleach activator	12%
	Sodium carbonate	6%
5	Soap	1%
	Brightener	0.5%
	Minors	to 100%

	<u>Liquid component detergent ingredient</u>	<u>Amount (by weight of liquid component)</u>
10	Nonionic surfactant	54%
	Solvent	12%
	Perfume	22%
	Water	2%
15	Minors	to 100%

### Example III

A pouch was made by the process described in example I which comprises the following  
20 liquid component and solid component.

<u>Solid component detergent ingredient</u>		<u>Amount (by weight of the solid component)</u>
5	Zeolite	64%
	Bleach	16%
	Chelating agent	2%
	Enzyme	10%
	Suds suppressor	1%
10	Sodium carbonate	4%
	Brightener	1%
	Minors	to 100%
<u>Liquid component detergent ingredient</u>		<u>Amount (by weight of liquid component)</u>
15	Nonionic surfactant	69%
	Solvent	179%
	Perfume	10%
	Water	3%
20	Minors	to 100%

Claims

1. A multi-compartment pouch made from a water-soluble film and having at least two compartments, said multi-compartment pouch comprises a composition comprising a solid component and a liquid component, wherein;  
5 (a) a first compartment comprises a solid component comprising (by weight of the solid component) at least 10% water-insoluble solid material; and  
(b) a second compartment comprises a liquid component.
- 10 2. A multi-compartment pouch according to claim 1, whereby said water-soluble film comprises a polyvinyl alcohol polymer.
3. A multi-compartment pouch according to any preceding claim, whereby, said solid component comprises (by weight of the solid component) at least 50% water insoluble  
15 material.
4. A multi-compartment pouch according to any preceding claim, whereby, said water insoluble material is a water insoluble building agent.
- 20 5. A multi-compartment pouch according to any preceding claim, whereby, said solid component comprises at least one member selected from the group consisting of chelating agent, hydrogen peroxide source, bleach activator, enzyme, brightener and suds suppressor.
- 25 6. A multi-compartment pouch according to any preceding claim, whereby said liquid component comprises at least two members selected from the group consisting of non-ionic surfactant, perfume, fatty acid or salt thereof, and solvent.
7. A multi-compartment pouch made from a water-soluble film and having at least two  
30 compartments, said multi-compartment pouch comprises a composition comprising a solid component and a liquid component, wherein;

- (a) a first compartment comprises a solid component comprising (by weight of the solid component) at least 15% particles comprising at least 20% surfactant; and
  - (b) a second compartment comprises a liquid component.
- 5    8. A multi-compartment pouch according to claim 7, whereby said solid component comprises at least 40% particles comprising at least 40% surfactant.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
8 November 2001 (08.11.2001)

PCT

(10) International Publication Number  
**WO 01/83657 A3**

(51) International Patent Classification<sup>7</sup>: **C11D 17/04**,  
B65D 65/46, C11D 3/37

(21) International Application Number: **PCT/US01/07707**

(22) International Filing Date: **9 March 2001 (09.03.2001)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:  
0010227.7 **28 April 2000 (28.04.2000)** **GB**

(71) Applicant (for all designated States except US): **THE PROCTER & GAMBLE COMPANY** [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SOMERVILLE-ROBERTS, Nigel, Patrick** [GB/GB]; 3, The Cloggs, Ponteland, Newcastle upon Tyne NE20 9UJ (GB). **DASQUE, Bruno, Matthieu** [FR/GB]; 3 Swindon Terrace, Newcastle upon Tyne NE6 5RB (GB). **POUNDS, Thomas, John** [GB/GB]; 5 Grange Gardens, Grange Road, Cambridge CB3 9AT (GB).

(74) Common Representative: **THE PROCTER & GAMBLE COMPANY**; c/o Reed, T., David, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(88) Date of publication of the international search report:  
**31 January 2002**

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **POUCHED COMPOSITIONS**

(57) Abstract: The present invention relates to a multi-compartment pouch made from a water-soluble film and having at least two compartments, said multi-compartment pouch comprises a composition comprising a solid component and a liquid component, wherein at least one compartment comprises a solid component and at least one compartment comprises a liquid component.

WO 01/83657 A3

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/07707

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C11D17/04 B65D65/46 C11D3/37

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C11D B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ, EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 973 416 A (KENNEDY SHAUN P) 27 November 1990 (1990-11-27) column 3, line 14-38; examples 1,2 ---	1,2,4-6
A	US 5 224 601 A (EDWARDS DAVID B ET AL) 6 July 1993 (1993-07-06) column 2, line 60 -column 4, line 39 column 5, line 63 -column 6, line 64 ---	1,2
A	EP 0 132 726 A (HENKEL KGAA) 13 February 1985 (1985-02-13) page 2, paragraph 2 page 5, line 27 -page 6, line 11 figures 1,2 ---	1,2
A	GB 2 000 177 A (AKZO NV) 4 January 1979 (1979-01-04) claims 1-11; examples 4,5 ---	1-5
-/-		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 July 2001

Date of mailing of the international search report

06. 11. 2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Bertran Nadal, J

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/07707

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p> <b>DATABASE WPI</b>  <b>Week 199850</b>  <b>Derwent Publications Ltd., London, GB;</b>  <b>AN 1998-584228</b>  <b>XP002172183</b>  <b>&amp; CA 2 199 221 A (BAYER CORP),</b>  <b>13 September 1997 (1997-09-13)</b>  <b>abstract</b>              -----         </p>	1,2

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US 01/07707

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1-6

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.



## FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

## 1. Claims: 1-6

A multi-compartment pouch made from a water-soluble film and having at least two compartments, said multi-compartment pouch comprises a composition comprising a solid component and a liquid component, wherein  
(a) a first compartment comprises a solid component comprising (by weight of the solid component) at least 10% water-insoluble solid material (e.g. building agent); and  
(b) a second compartment comprises a liquid component.

## 2. Claims: 7, 8

A multi-compartment pouch made from a water-soluble film and having at least two compartments, said multi-compartment pouch comprises a composition comprising a solid component and a liquid component, wherein  
(a) a first compartment comprises a solid component comprising (by weight of the solid component) at least 15% particles comprising at least 20% surfactant; and  
(b) a second compartment comprises a liquid component.

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/07707

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4973416	A	27-11-1990	JP 2155999 A	15-06-1990
US 5224601	A	06-07-1993	US 5080226 A	14-01-1992
			AP 245 A	04-03-1993
			AP 325 A	09-03-1994
			AP 280 A	03-08-1993
			AP 358 A	03-09-1994
			AP 357 A	03-09-1994
			AP 356 A	03-09-1994
			AT 150253 T	15-04-1997
			AT 184746 T	15-10-1999
			AT 184748 T	15-10-1999
			AT 184747 T	15-10-1999
			AT 184749 T	15-10-1999
			AU 7611491 A	07-11-1991
			AU 8039591 A	23-01-1992
			AU 8039691 A	23-01-1992
			AU 8039791 A	23-01-1992
			AU 8039891 A	23-01-1992
			AU 8039991 A	23-01-1992
			AU 647154 B2	17-03-1994
			AU 8097791 A	18-02-1992
			AU 647155 B2	17-03-1994
			AU 8097891 A	18-02-1992
			AU 651981 B2	11-08-1994
			AU 8105291 A	18-02-1992
			AU 647165 B2	17-03-1994
			AU 8200091 A	18-02-1992
			AU 656325 B2	02-02-1995
			AU 8220391 A	18-02-1992
			BE 1003800 A5	16-06-1992
			BR 9101835 A	17-12-1991
			BR 9105833 A	29-09-1992
			BR 9105834 A	29-09-1992
			BR 9105835 A	29-09-1992
			BR 9105836 A	29-09-1992
			BR 9105837 A	29-09-1992
			CA 2041313 A1	03-11-1991
			CA 2065159 A1	19-01-1992
			CA 2066243 A1	19-01-1992
			CA 2066405 C	17-06-1997
			CA 2066419 C	17-06-1997
			CA 2066424 C	20-09-1994
			CH 684468 A5	30-09-1994
			CN 1058317 A	05-02-1992
			CN 1058318 A	05-02-1992
			CN 1058319 A	05-02-1992
			CN 1058191 A ,B	29-01-1992
			CN 1058320 A	05-02-1992
			CS 9101249 A2	17-12-1991
			CS 9102215 A3	19-02-1992
			CS 9102216 A3	19-02-1992
EP 0132726	A	13-02-1985	DE 3326249 A1	31-01-1985
			AT 37692 T	15-10-1988
			DE 3474432 D1	10-11-1988
			EP 0132726 A2	13-02-1985
			ES 280634 U	16-02-1985

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/07707

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2000177	A	04-01-1979	AT 374826 B 12-06-1984
			AT 462378 A 15-10-1983
			BE 868474 A1 16-10-1978
			CH 639416 A5 15-11-1983
			DE 2827571 A1 11-01-1979
			DK 285078 A ,B, 28-12-1978
			ES 476032 A1 01-07-1980
			FR 2396076 A1 26-01-1979
			IT 1097284 B 31-08-1985
			NL 7805293 A ,B, 29-12-1978
			NO 782178 A ,B, 28-12-1978
			SE 439780 B 01-07-1985
			SE 7807255 A 28-12-1978
CA 2199221	A	13-09-1997	CA 2199221 A1 13-09-1997

